LOGIK



I-Tech multi-cell optic provides excellent glare control with BS EN-12464 compliance Suitable for office installations and general or task area lighting Outstanding uniformity with up to 3m spacing



LOGIK





- Suitable for office installations and general or task area lighting
- Outstanding uniformity with up to 3m spacings
- TP(a) rated optic
- Gear options of DALI and Emergency
- CRI: Ra>80
- Up to 130 lumens per Watt efficacy
- 60,000 hours lifetime (L80/B20)










Recessed module for low glare and office areas

Order Code	Description	lm	W	lm/W	kg
LGK200NW	16W - 4000K	2000	16	125	2.90
LGK300NW	23W - 4000K	3000	23	130	2.90
LGK400NW	31W - 4000K	4000	31	129	2.90

Dimensions

Order Code	A (mm)	B (mm)	C (mm)	Cut Out
LGK200NW	595	595	42	595x595
LGK300NW	595	595	42	595x595
LGK400NW	595	595	42	595x595



CONSTRUCTION

- Semi-opal high performance polycarbonate optic
- Steel frame, finished in white (RAL 9016)
- Supplied as standard with neutral white (4000K) LED

OPTIONS


D	Dimmable DALI
МЗ	3 hours integrated emergency
АЗ	Emergency self test
D3	DALL self test

INSTALLATION NOTES

Recessed lay-in for exposed T-Bar ceiling grid. Brackets available for plasterboard mount. Frame available for metal pan ceilings

TO SPECIFY

Recessed multi-cell module to EN 12464 as per Tamlite LOGIK range



Lighting for a Living

Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777 E. sales@tamlite.co.uk W. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:















& Leisure







Healthcare

Industrial

Office

Sports

Urban

Communal

Education

Emergency