

Driver gear options of DALI, Emergency and Ready2Mains dimming available


Sealed to IP65 rating for medical and cleanrooms

Wide range of diffusers



Lighting for a Living





- Full range of gear options including DALI and emergency are available
- CRI: Ra>80
- Up to 111 lumens per Watt efficacy
 50,000 hours lifetime (L70/B50)










Recessed sealed module

Order Code	Description	lm	W	lm/W	kg
TSMXOP66390NW	35W - 4000K	3900	35	111	6.90
TSMXOP123390NW	35W - 4000K	3900	35	111	10.20
TSMXOP126780NW	70W - 4000K	7800	70	111	12.50

Dimensions

Order Code	A (mm)	B (mm)	C (mm)
TSMXOP66390NW	595	595	76
TSMXOP123390NW	1195	295	76
TSMXOP126780NW	1195	595	76



CONSTRUCTION

- Steel body finished in white (RAL
- Self-tightening fixing clips
- Glass, micro-prism, opal or prismatic polycarbonate diffuser options
- Extruded aluminium frame with silicone gasket
- Supplied as standard with neutral white (4000K) LED

OPTIONS


M3	3 hours integrated emergency
A3	Auto self test
D3	DALI self test
D	DALI dimming control gear
WW	Warm white (3000K)
CW	Cool white (5000K)

INSTALLATION NOTES

Recessed lay-in for exposed 25mm ceiling grid. Brackets available for plasterboard mount. Option available for metal pan ceilings

TO SPECIFY

Recessed IP65 module with opal diffuser as per Tamlite TX range



Tamlite Lighting Sales Centre

Tamlite Field Sales Centre, Park Farm Industrial Estate, Redditch, Worcestershire, B98 0HU

T. 01527 517 777E. sales@tamlite.co.ukW. tamlite.co.uk

Over 50 years lighting for a Living

As a UK manufacturer we have one of the widest lighting ranges across:























Communal Education

n Em

Emergency

Healthcare

Industrial

Office

Retail & Leisure

Sports

Urban Warehouse & Logistics