

# BRONX

Corner mounted LED



### Features:

- Robust steel, corner mounted LED solution
- Choice of two sizes to suit most applications
- White, grey or black body colour options
- Driver gear options of DALI, Emergency and Ready2Mains dimming available
- CRI: Ra>80
- Up to 66 lumens per Watt efficacy
- 50,000 hours lifetime (L70/B50)

### Construction:

- Steel body finished in white (RAL 9016)
- Supplied with micro-linear frosted diffuser
- Supplied as standard with neutral white (4000K) LED

### Options:

- HFR - High frequency analogue dimming
- HFD - Digital dimmable version
- HFSD - Dimmable microwave movement sensor
- M3 - 3 hours integrated emergency
- A3 - Emergency self test
- WW - Warm white (3000K)
- B - Black (RAL 9005)
- Gy - Grey (RAL 9006)

# BRONX

Corner mounted LED

### Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
BX42330NW	50W - 4000K	3300	50	66	14.2
BX52500NW	75W - 4000K	4900	75	65	16.8

### Dimensions

All dimensions are in millimetres

Order code	A	B	C
BX42330NW	1260	205	205
BX52500NW	1530	205	205



### Installation instructions:

Wall mounting via rear mounting holes

### To specify:

Steel, corner mounted as per Tamlite BRONX range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.