

CORNICE

LED Corner light



Features:

- High quality aluminium extrusions
- Corner mounted profile is ideal for corridor and walkway areas
- Suspended mounted option
- Driver gear options of DALI, Emergency and Ready2Mains dimming available
- CRI: Ra>80
- Up to 111 lumens per Watt efficacy
- 50,000 hours lifetime (L70/B50)

Construction:

- Extruded aluminium body finished in white (RAL 9016)
- Opal polycarbonate diffuser
- Rear or 2 x side cable entry
- High output micro-prism diffuser option
- Supplied as standard with neutral white (4000K) LED

Options:

- HFR - High frequency analogue dimming
- HFD - Digital dimmable version
- M3 - 3 hours integrated emergency
- AST - Emergency self test
- WW - Warm white (3000K)
- CW - Cool white (5000K)
- MPRM - Micro-prism diffuser

CORNICE

LED Corner light

Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
CORCM3240NW	23W - 4000K	2400	23	104	2.3
CORCM4300NW	28W - 4000K	3000	28	107	3.0
CORCM5420NW	38W - 4000K	4200	38	111	3.7

Dimensions

All dimensions are in millimetres

Order code	A	B	C
CORCM3240NW	875	101	64
CORCM4300NW	1165	101	64
CORCM5420NW	1455	101	64



Installation instructions:

Wall or ceiling fix base mounting with rear or side cable entry

To specify:

LED Corner wall luminaire as per Tamlite CORNICE range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.