

# ELAN

Surface linear module with high performance optic



### Features:

Tamlite I-Tech diffuser designed for low glare reduction to BS EN-12464 compliance  
High performance opal optic for high efficacy and glare control  
Suitable for office, schools and hospital applications  
CRI: Ra>80  
Up to 117 lumens per Watt efficacy  
50,000 hours lifetime (L70/B50)

### Construction:

Extruded aluminium body finished  
in white (RAL 9016), grey (RAL  
9006) or black (RAL 9005)  
Semi-opal micro prism I-Tech diffuser with multi layer control  
Polycarbonate end caps  
Supplied as standard with neutral white (4000K) LED

### Options:

V202 - Integral PIR device  
V203 - Integral PIR dimming device  
D - Dimmable DALI  
M3 - 3 hours integrated emergency  
A3 - Emergency self test  
D3 - DALI self test  
WW - Warm white (3000K)  
CW - Cool white (5000K)

# ELAN

Surface linear module with high performance optic

### Order Codes


All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
ELN421NW	18W - 4000K	2100	18	117	4.10
ELN521NW	18W - 4000K	2100	18	117	5.35
ELN430NW	26W - 4000K	3000	26	115	4.10
ELN530NW	26W - 4000K	3000	26	115	5.35
ELN440NW	35W - 4000K	4000	35	114	4.10
ELN540NW	35W - 4000K	4000	35	114	5.35

### Dimensions

All dimensions are in millimetres

Order code	A	B	C
ELN421NW	1120	120	80
ELN521NW	1450	120	80
ELN430NW	1120	120	80
ELN530NW	1450	120	80
ELN440NW	1120	120	80
ELN540NW	1450	120	80



### Installation instructions:

Surface mount via rear entry fixings or suspended via 3.0m wire suspension kit

### To specify:

Surface linear module as per Tamlite ELAN range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.