

# FRESCO

Extruded aluminium LED bollard



### Features:

Ideal for pathways and pedestrian areas

Symmetric distribution

Surface mounted utilising J bolts

CRI: Ra>80

Up to 65 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

### Construction:

Extruded aluminium body finished in black (RAL 9005)

Root mounted kit also available

Integral driver

Supplied as standard with neutral white (4000K) LED

### Options:

M3 - 3 hours integrated emergency

# FRESCO

Extruded aluminium LED bollard

### Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
FREL23NW	23W - 4000K	1500	23	65	5.7

### Dimensions

All dimensions are in millimetres

Order code	C	Diameter
FREL23NW	1000	180

### Installation instructions:

Surface mount utilising J bolt assembly and wired via a three way terminal block. Please ensure correct ground preparations are applied before installation

### To specify:

LED bollard as per Tamlite FRESCO range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.



Tamlite Sales Centre.  
Tel: 01527 517777  
Fax: 01527 517666  
e-mail: [sales@tamlite.co.uk](mailto:sales@tamlite.co.uk)

Tamlite Technical.  
Tel: 01952 292441  
Fax: 01952 292155  
e-mail: [technical@tamlite.co.uk](mailto:technical@tamlite.co.uk)

