

FRESCO

Extruded aluminium LED bollard



5 YR

IP54



Features:

Ideal for pathways and pedestrian areas

Symmetric distribution

Surface mounted utilising J bolts

CRI: Ra>80

Up to 65 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

Construction:

Extruded aluminium body finished in black (RAL 9005)

Integral driver

Supplied as standard with neutral white (4000K) LED

Options:

M3 - 3 hours integrated emergency

FRESCO

Extruded aluminium LED bollard

Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
FREL23NW	23W - 4000K	1500	23	65	5.7

Dimensions

All dimensions are in millimetres

Order code	C	Diameter
FREL23NW	1000	180

Installation instructions:

Surface mount utilising J bolt assembly and wired via a three way terminal block. Please ensure correct ground preparations are applied before installation

To specify:

LED bollard as per Tamlite FRESCO range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.



Tamlite Sales Centre.
Tel: 01527 517777
Fax: 01527 517666
e-mail: sales@tamlite.co.uk

Tamlite Technical.
Tel: 01952 292441
Fax: 01952 292155
e-mail: technical@tamlite.co.uk

