

# HENLEY

Die-cast aluminium LED bollard



5 YR

IP54



### Features:

Modern styling for use in urban lighting projects

11W LED module provides long life and maintenance-free solution

Choice of square or circular designs

CRI: Ra>80

Up to 27 lumens per Watt efficacy

30,000 hours lifetime (L70/B50)

### Construction:

Die-cast aluminium body finished in black

Opal acrylic diffuser

Stainless steel tamper-proof fixing screws

Integral driver

Separate base fixing

Supplied as standard with neutral white (4000K) LED

### Options:

No options available

# HENLEY

Die-cast aluminium LED bollard

### Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
TE-HEN50SQNW	11W - 4000K	300	11	27	5.3
TE-HEN50CNW	11W - 4000K	300	11	27	4.2

### Dimensions

All dimensions are in millimetres

Order code	A	B	C
TE-HEN50SQNW	225	225	1000
TE-HEN50CNW			1000

### Installation instructions:

Fixed via surface mounted flange plate and wired via 3 pole connection block. Please ensure correct ground preparations are applied before installation

### To specify:

LED bollard as per Tamlite HENLEY range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.



Tamlite Sales Centre.  
Tel: 01527 517777  
Fax: 01527 517666  
e-mail: sales@tamlite.co.uk

Tamlite Technical.  
Tel: 01952 292441  
Fax: 01952 292155  
e-mail: technical@tamlite.co.uk

