

HORIZON COMFORT

Recessed LED module with indirect/direct output



Features:

Tamlite I-Tech diffuser designed for low glare reduction to BS EN-12464 compliance

Suitable for use in VDU areas such as offices, schools and universities. High output version also ideal for Retail and Commercial areas

3 different outputs for low, medium or high spacing layouts

Gear options of DALI, Emergency and Ready2Mains dimming available

CRI: Ra>80

Up to 130 lumens per Watt efficacy

>50,000 hours lifetime (L80/B10)

Construction:

Steel body finished in white (RAL 9016)

Opal polycarbonate diffuser

Supplied as standard with neutral white (4000K) LED

Options:

V202 - Integral PIR device

V203 - Integral PIR dimming device

D - Dimmable DALI

M3 - 3 hours integrated emergency

A3 - Emergency self test

D3 - DALI self test

WW - Warm white (3000K)

CW - Cool white (5000K)

HORIZON COMFORT

Recessed LED module with indirect/direct output

Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
TIDO66220NW	18W - 4000K	2200	18	122	5.40
TIDO66300NW	23W - 4000K	3000	23	130	5.40
TIDO66450NW	36W - 4000K	4500	36	125	5.40

Dimensions

All dimensions are in millimetres

Order code	A	B	C
TIDO66220NW	595	595	135
TIDO66300NW	595	595	135
TIDO66450NW	595	595	135

Installation instructions:

Recessed lay-in for exposed T ceiling grid, frame available for plasterboard mount

To specify:

Recessed indirect/direct LED module with glare control diffuser as per Tamlite HORIZON range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.