

I LINE MODULES

Pre-wired LED continuous lighting system



5 YR

IP20



Features:

Ideal solution for retail and industrial applications

DALI dimming control gear as standard with emergency option available

Simple easy to fit lock in system allows a flexible and speedy installation

High efficiency LED light module with a choice of wide, narrow or double asymmetric optics

Three power options are available 35W, 55W and 75W

CRI: Ra>80

Up to 156 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

Construction:

Extruded aluminium body finished in white (RAL 9016)

Simple push-fit into the trunking rail

Supplied with a DALI dimmable driver as standard

Supplied as standard with neutral white (4000K) LED

Options:

No options available

I LINE MODULES

Pre-wired LED continuous lighting system

Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
ILM535DA11	35W - 4000K	5450	35	156	2.1
ILM535WB11	35W - 4000K	5350	35	153	2.1
ILM535NB11	35W - 4000K	5450	35	156	2.1
ILM555DA11	55W - 4000K	8300	55	151	2.1
ILM555WB11	55W - 4000K	8150	55	148	2.1
ILM555NB11	55W - 4000K	8300	55	151	2.1
LM575DA11	75W - 4000K	10800	75	144	2.1
ILM575WB11	75W - 4000K	10600	75	141	2.1
ILM575NB11	75W - 4000K	10800	75	144	2.1

Dimensions

All dimensions are in millimetres

Order code	A	B	C
ILM535DA11	1416	73	80
ILM535WB11	1416	73	80
ILM535NB11	1416	73	80
ILM555DA11	1416	73	80
ILM555WB11	1416	73	80
ILM555NB11	1416	73	80
LM575DA11	1416	73	80
ILM575WB11	1416	73	80
ILM575NB11	1416	73	80

To specify:

Pre-wired LED linear lighting system range as per Tamlite I LINE Modules

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.