

MICRO LED XL

High performance LED batten



Features:

- High output LEDs for up to 16 metre mounting height
- Ideal for industrial and commercial applications
- Wide beam or narrow beam versions available
- Full range of gear options including dimmable, DALI and emergency available
- CRI: Ra>80
- Up to 113 lumens per Watt efficacy
- 100,000 hours lifetime (L80/B10)

Construction:

- Extruded aluminium body finished in white (RAL 9010)
- Polycarbonate extruded diffuser
- Pressed steel spine with clip and fix
- Polycarbonate end caps
- Integral driver
- Rear BESA fixings and cable entry
- Supplied as standard with Wide beam (80°) clear lens
- Supplied as standard with neutral white (4000K) LED

Options:

- HFR - High frequency analogue dimming
- HFD - Digital dimmable version
- DALI - DALI dimming control gear
- M3 - 3 hours integrated emergency
- AST - Emergency self test
- WW - Warm white (3000K)
- CW - Cool white (5000K)
- DL - Daylight (6500K)

MICRO LED XL

High performance LED batten

Order Codes


All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
MLEDXL5950NW	84W - 4000K - Wide beam (80°) clear lens	9500	84	113	4.2
MLEDXL51200NW	128W - 4000K - Wide beam (80°) clear lens	12000	128	94	4.2

Dimensions

All dimensions are in millimetres

Order code	A	B	C
MLEDXL5950NW	1414	62	75
MLEDXL51200NW	1414	62	75



Installation instructions:

A range of mounting options including BESA fixing and wire suspension

To specify:

High performance extruded aluminium LED batten as per MICRO LED XL

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.