

RACKLINE

Linear light system with racking aisle optic



5 YR

IP20



Features:

- Continuous linear system suitable for warehouse or retail areas
- High performance optic with narrow distribution, ideal for racking aisles
- Standard lumen outputs or specific user-defined outputs
- Joining brackets to enable single runs up to 100m
- CRI: Ra>80
- Up to 162 lumens per Watt efficacy
- 50,000 hours lifetime (L70/B50)

Construction:

- Extruded aluminium body finished in white (RAL 9016)
- Plastic clear optic lens
- Steel joining bracket
- Integral driver
- Supplied in 1500mm sections as standard
- Supplied as standard with neutral white (4000K) LED

Options:

- D - Dimmable DALI
- D3 - DALI self test
- M3 - 3 hours integrated emergency
- A3 - Emergency self test
- CW - Cool white (5000K)
- DL - Daylight (6500K)
- O - Opal diffuser
- WB - Wide beam
- NB - Narrow beam

RACKLINE

Linear light system with racking aisle optic

Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
TRL5400NW	26W - 4000K	4000	26	154	2.96
TRL5600NW	40W - 4000K	6000	40	150	2.96
TRL3800NW	52W - 4000K	8000	52	154	5.92
TRL5900NW	62W - 4000K	9000	62	145	2.96
TRL51200NW	74W - 4000K	12000	74	162	2.96
TRL41200NW	78W - 4000K	12000	78	154	8.80
TRL31200NW	80W - 4000K	12000	80	150	5.92
TRL41800NW	120W - 4000K	18000	120	150	8.80
TRL31800NW	124W - 4000K	18000	124	145	5.92
TRL32400NW	148W - 4000K	24000	148	162	5.92
TRL42700NW	186W - 4000K	27000	186	145	8.80
TRL43600NW	222W - 4000K	36000	222	162	8.80

Dimensions

All dimensions are in millimetres

Order code	A	B	C
TRL5400NW	1500	65	60
TRL5600NW	1500	65	60
TRL3800NW	3000	65	60
TRL5900NW	1500	65	60
TRL51200NW	1500	65	60
TRL41200NW	4500	65	60
TRL31200NW	3000	65	60
TRL41800NW	4500	65	60
TRL31800NW	3000	65	60
TRL32400NW	3000	65	60
TRL42700NW	4500	65	60
TRL43600NW	4500	65	60



Installation instructions:

Surface mount via rear entry or suspended via wire suspension

To specify:

Pre-wired linear lighting system range as per Tamlite RACKLINE Modules

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.