

# TC LIGHTING COLUMNS

Aluminium lighting columns



### Features:

- Hot dipped galvanised to BS729
- Tapered conical design
- Traditional tubular style with semi-flush door
- Smooth anodised finish
- Wide range of brackets and spigots available

### Construction:

- Mild galvanised steel or aluminium alloy tubing
- Designed to BS5649 series 1300
- Root section externally bitumen coated

### Options:

- No options available

# TC LIGHTING COLUMNS

Aluminium lighting columns

### Order Codes

All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
TC6A	6000mm Aluminium				22.8
TC5A	5000mm Aluminium				18.7
TC4A	4000mm Aluminium				10.6
TC3A	3500mm Aluminium				9.2
TC8MLD	6000mm Medium duty				85
TC6M	6000mm Light duty steel				51
TC5M	5000mm Light duty steel				40
TC4M	4000mm Light duty steel				33
TC3M	3000mm Heavy duty steel				28
TC8MHD	8000mm Heavy duty steel				100
TC6MHD	6000mm Heavy duty steel				68

### Dimensions

All dimensions are in millimetres

Order code	A	B	C
TC6A	6000	120	6
TC5A	5000	120	5
TC4A	4000	114	4
TC3A	3500	114	3.5
TC8MLD	6000	89	8
TC6M	6000	76	6
TC5M	5000	76	5
TC4M	4000	76	4
TC3M	3000	76	3
TC8MHD	8000	114	8
TC6MHD	6000	89	6

### Installation instructions:

Surface mount via flange plate and bolt-template

### To specify:

Conical aluminium lighting column as per Tamlite TCA range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.



**Tamlite Sales Centre.**  
**Tel: 01527 517777**  
**Fax: 01527 517666**  
**e-mail: sales@tamlite.co.uk**

Tamlite Technical.  
 Tel: 01952 292441  
 Fax: 01952 292155  
 e-mail: technical@tamlite.co.uk

