

# TX

LED Recessed sealed module



### Features:

Sealed to IP65 rating for medical and cleanrooms

Wide range of diffusers

Driver gear options of DALI, Emergency and Ready2Mains dimming available

CRI: Ra>80

Up to 111 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

### Construction:

Steel body finished in white (RAL 9016)

Self-tightening fixing clips

Glass, VDT, micro-prism, opal or prismatic polycarbonate diffuser options

Silicone gasket

Supplied as standard with neutral white (4000K) LED

### Options:

HFR - High frequency analogue dimming

HFD - Digital dimmable version

DALI - DALI dimming control gear

M3 - 3 hours integrated emergency

AST - Emergency self test

WW - Warm white (3000K)

# TX

LED Recessed sealed module

### Order Codes


All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
TSMXOP66390NW	35W - 4000K	3900	35	111	6.9
TSMXOP123390NW	35W - 4000K	3900	35	111	10.2
TSMXOP126780NW	70W - 4000K	7800	70	111	12.5

### Dimensions

All dimensions are in millimetres

Order code	A	B	C
TSMXOP66390NW	595	595	76
TSMXOP123390NW	1195	295	76
TSMXOP126780NW	1195	595	76



### Installation instructions:

Recessed lay-in for exposed 25mm ceiling grid. Brackets available for plasterboard mount. Frame available for metal pan ceilings

### To specify:

Recessed IP65 LED module with opal diffuser as per Tamlite TX LED range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.